


# MAKESAFE PRODUCT SPECS

	PTB-V120-P1	PTB-V240-P1	PTB-V240-P3
Rated Input Voltage	120 VAC 1 PH, 60 Hz (50 Hz options available)	240 VAC 1 PH, 60 Hz (50 Hz options available)	240 VAC 3 PH, 60 Hz (50 Hz options available)
Rated Horsepower (UL508)	1.5 HP	3.0 HP	5.0 HP
Rated Current (UL508)	15A	15A	15A
Approvals 	UL508: Industrial Control Devices CSA #14-13: Industrial Control Equipment LISTING NUMBER: E114885		
Dimensions (main enclosure only)	7.25" L x 5.0" W x 2.3" H (185 mm x 127 mm x 57 mm)		
Dimensions (std. control panel)	3.0" x 2.0" x 0.9" in. (76.20 mm x 50.80 mm x 22.86 mm)		
Weight (main enclosure)	3 lbs (1.4 kg)		3.3 lbs (1.5 kg)
Rated Output Voltage (normal operation)	120 VAC	240 VAC	
Rated Output Voltage (during braking)	15 - 90 VDC	30 - 180 VDC	30 - 240 VDC
Standard Connector Type	NEMA 5-15 (custom and international options available)	NEMA 6-15 (custom and international options available)	NEMA L15-20 (custom and international options available)
Notes: 1. This device is only compatible with direct-powered induction motor tools. To verify compatibility, see compatibility guide in product manual, available at <a href="http://www.makesafetools.com">www.makesafetools.com</a> . 2. Suitable for connection in the field to a branch circuit rated not more than 20 amperes and capable of delivering not more than 5,000 rms symmetrical amperes			

CLICK HERE TO  
RETURN TO THE  
MAIN MENU